

# FORTUS 900mc™



**Designed and built for size, throughput, precision and repeatability.**

The Fortus 900mc™ was specifically designed for direct digital manufacturing. Not only has the build envelope dramatically increased in size over previous Fortus systems, there are significant differences in its mechanical, electromechanical and electrical systems. Specifically, the head gantry is driven by ball-screw technology resulting in more accurate parts with improvements in predictability and repeatability. Additionally, the control software has been modified to leverage the system's hardware advancements. These features deliver greater throughput, accuracy, repeatability, and reliability.

Like all Fortus 3D Production Systems, the Fortus 900mc uses stable thermoplastics that continue to outperform nearly all competing technologies in accuracy and repeatability. Proven FDM (Fused Deposition Modeling) technology manufactures Real Parts™ in production-grade thermoplastics that are ideal for conceptual modeling, functional prototyping, manufacturing tools, and end-use parts.

**Learn more about the Fortus 900mc at [stratasys.com](https://www.stratasys.com)**



## System Specifications

BASE SYSTEM CONFIGURATION																																																							
<b>Build Envelope (XYZ)</b>	36 x 24 x 36 inch (914.4 x 609.6 x 914.4 mm) Platen supports two (2) build zones for either a small or large build sheet																																																						
<b>Material Delivery</b>	Two (2) Build material canisters 92 in <sup>3</sup> (1508 cc) Two (2) Support material canisters 92 in <sup>3</sup> (1508 cc) Auto changeover between canisters																																																						
MATERIAL OPTIONS																																																							
<b>Layer Thickness:</b>	<table border="1"> <thead> <tr> <th>ABSi</th> <th>ABS-M30</th> <th>ABS-M30i</th> <th>ABS-ESD7</th> <th>PC-ABS</th> <th>PC-ISO</th> <th>PC</th> <th>ULTEM® 9085</th> <th>PPSF</th> </tr> </thead> <tbody> <tr> <td>X</td> <td>X</td> <td>X</td> <td></td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td></td> </tr> <tr> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> </tr> <tr> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td>X</td> <td></td> <td>X</td> <td></td> <td></td> </tr> </tbody> </table>	ABSi	ABS-M30	ABS-M30i	ABS-ESD7	PC-ABS	PC-ISO	PC	ULTEM® 9085	PPSF	X	X	X		X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X		X																				
ABSi	ABS-M30	ABS-M30i	ABS-ESD7	PC-ABS	PC-ISO	PC	ULTEM® 9085	PPSF																																															
X	X	X		X	X	X	X																																																
X	X	X	X	X	X	X	X	X																																															
X	X	X	X	X		X																																																	
<b>Support Structure:</b>	<table border="1"> <thead> <tr> <th>Soluble</th> <th>Soluble</th> <th>Soluble</th> <th>Soluble</th> <th>Soluble</th> <th>BASS</th> <th>BASS, Soluble</th> <th>BASS</th> <th>BASS</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Soluble	Soluble	Soluble	Soluble	Soluble	BASS	BASS, Soluble	BASS	BASS																																													
Soluble	Soluble	Soluble	Soluble	Soluble	BASS	BASS, Soluble	BASS	BASS																																															
<b>Available Colors:</b>	<table border="1"> <thead> <tr> <th>Trans-lucent Natural</th> <th>Ivory</th> <th>Ivory</th> <th>Black</th> <th>Black</th> <th>Trans-lucent Natural</th> <th>White</th> <th>Tan</th> <th>Tan</th> </tr> </thead> <tbody> <tr> <td>Trans-lucent Amber</td> <td>White</td> <td></td> <td></td> <td></td> <td>White</td> <td></td> <td>Black</td> <td></td> </tr> <tr> <td>Trans-lucent Red</td> <td>Black</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Red</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Blue</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Dark Grey</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Trans-lucent Natural	Ivory	Ivory	Black	Black	Trans-lucent Natural	White	Tan	Tan	Trans-lucent Amber	White				White		Black		Trans-lucent Red	Black									Red									Blue									Dark Grey							
Trans-lucent Natural	Ivory	Ivory	Black	Black	Trans-lucent Natural	White	Tan	Tan																																															
Trans-lucent Amber	White				White		Black																																																
Trans-lucent Red	Black																																																						
	Red																																																						
	Blue																																																						
	Dark Grey																																																						
OTHER SPECIFICATIONS																																																							
<b>System Size/Weight</b>	109.1 x 66.3 x 79.8 inches (2772 x 1683 x 2027 mm)																																																						
<b>System Size with manufacturing light tower</b>	109.1 x 66.3 x 89.8 inches (2772 x 1683 x 2281 mm)																																																						
<b>Achievable Accuracy</b>	Parts are produced within an accuracy of +/- .0035 inch or +/- .0015 inch per inch whichever is greater (+/- .089 mm or +/- .0015 mm per mm whichever is greater)* <small>*Note: Accuracy is geometry dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield. See Fortus 900mc accuracy white paper for more information.</small>																																																						
<b>Network Communication</b>	10/100 base T connection. Ethernet protocol.																																																						
<b>Operator Attendance</b>	Limited attendance for job start and stop required.																																																						
<b>Operating Environment<sup>1</sup></b>	Maximum room temperature of 85°F (29°C). Maximum room humidity of 80%																																																						
<b>Power Requirements<sup>1</sup></b>	230 VAC (three phase) 50/60Hz, Voltage fluctuation +/- Current 40A																																																						
<b>Additional Requirements<sup>1</sup></b>	Compressed Air Required																																																						
<b>Regulatory Compliance<sup>1</sup></b>	CE																																																						
<b>Software</b>	All Fortus systems include Insight™ and Control Center™ job processing and management software.																																																						

<sup>1</sup>See Fortus 900mc Site Prep Guide for detailed power and environmental specs

Stratasys | [www.stratasys.com](http://www.stratasys.com) | [info@stratasys.com](mailto:info@stratasys.com)

7665 Commerce Way  
Eden Prairie, MN 55344  
+1 888 480-3548 (US Toll Free)  
+1 952 937-3000 (Intl)  
+1 952 937-0070 (Fax)

2 Holtzman St.,  
Science Park, PO Box 2496  
Rehovot 76124, Israel  
+972 74 745-4000  
+972 74 745-5000 (Fax)

Local Street Address  
City, State, Zip  
Phone #  
Fax #

©2013 Stratasys Inc. All rights reserved. Stratasys, FDM and Fortus are registered trademarks and Fused Deposition Modeling, FDM Technology, Fortus 250mc, Fortus 360mc, Fortus 400mc, Fortus 900mc, Insight and Control Center are trademarks of Stratasys Inc., registered in the United States and other countries. \*ULTEM 9085 is a trademark of SABIC Innovative Plastics IP BV. All other trademarks are the property of their respective owners. Product specifications subject to change without notice. Fortus900mcSellSheet-US-1013

### At the core:

#### Advanced FDM Technology™

Fortus systems are based on Stratasys FDM — Fused Deposition Modeling™ — technology. FDM is the industry's leading additive manufacturing technology, and the only one that uses production grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization, and high impact applications.

#### No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems don't produce noxious fumes, chemicals, or waste.

#### No special skills needed

Fortus 3D Production Systems are easy to operate and maintain compared to other additive fabrication systems because there are no messy powders or resins to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

#### Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes. Accuracy. Strength. The best way to see the advantages of a Fortus 3D Production System is to have your own part built on a Fortus system. Get your free part at: [stratasys.com](http://stratasys.com)